

SUMMARY

Wires

| | |
|---------|---|
| Low | 2 |
| High | 0 |
| Coax | 0 |
| Triax | 0 |
| Quad | 0 |
| Fiber | 0 |
| Fluidic | 0 |



Image is for illustrative purpose only

Series

| | |
|------------------|------------------|
| Termination type | Female print PCB |
| IP rating | 50 |
| Cable Ø | 0.00 - 0.00 mm |
| Matching parts | |
| Status | active |
| Alternative part | |

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|---|
| Shell Style/Model | EP*: Elbow receptacle for printed circuit |
| Keying | 1 key (alpha=0, plug: male contacts, receptacle: female contacts) |
| Housing Material | PPS (Polyphenylene) shell, other pieces nickel plated brass |
| Cable Fixing | ∅ 0 - 0 mm |
| Variant | |

Performance

| | |
|---------------|--|
| Configuration | 0.302 : 2 Low Voltage |
| Insulator | L: PEEK (UL 94 / V-0/3.2, depends on material thickness) |
| Rated Current | 2 Amps |

Specifications

| |
|---|
| Contact Type: Print (straight) |
| Vtest (contact-shell): 950 V (AC), 1340 V (DC) |
| Vtest (contact-contact): 1000 V (AC), 1400 V (DC) |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

IP Rating: 50

DRAWINGS

Draws



Dimensions

| | A | D | H | I | K | L | N | R |
|-----|------|------|------|------|------|------|------|------|
| mm. | 6.8 | 11.5 | 3.5 | 7 | 8.7 | 19 | 7.1 | 5.08 |
| in. | 0,27 | 0,45 | 0,14 | 0,28 | 0,34 | 0,75 | 0,28 | 0,20 |

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.