

PHG.00.302.CLLD35

SUMMARY

Wires

Fluidic

 Low
 2

 High
 0

 Coax
 0

 Triax
 0

 Quad
 0

 Fiber
 0

Series 00

Termination type Female solder

IP rating 50

 Cable Ø
 2.80 - 3.50 mm

 Matching parts
 FGG.00.302.CLAD35

0

Status active

Alternative part



Image is for illustrative purpose only

TECHNICAL DETAILS

Mechanics

Shell Style/Model PH*: Free receptacle, cable collet

Keying 1 key (alpha=0, plug: male contacts, receptacle: female contacts)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing D35: 2.8 - 3.5 mm

Variant

Performance

Configuration 0.302 : 2 Low Voltage

Insulator L: PEEK (UL 94 / V-0/3.2, depends on material thickness)

Rated Current 5 Amps

Specifications

Contact Type: Solder Max. Matings: 5000

Contact Dia.: 0.5 mm (0.02in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 0.4 mm (0.016in)

Max. Solid Conductor: 0.09 mm² (AWG 28) Max. Stranded Conductor: 0.05 mm² (AWG 30)

R (max): 8.7 mOhm


Vtest (contact-shell): 950 V (AC), 1340 V (DC) Vtest (contact-contact): 1000 V (AC), 1400 V (DC)

Others

IP Rating: 50

DRAWINGS

Draws







Dimensions

	А	L	S1	S2
mm.	6.8	26	5.5	5
in.	0,27	1,02	0,22	0,20

RECOMMENDED BY LEMO

Tools

None

Cables

CMN.02.T28.030PGCE	PVC	GREY	-
--------------------	-----	------	---

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

CMN.02.T28.030PGZE		Grey	=
CMN.02.T28.030PNCE	PVC	Black	
CMN.02.T28.030PNZE			-
002 080	PVC	Grey	
CCX.50.RG1.74U30B	TFE	White	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.