

# PHG.0B.307.CLLD56

### **SUMMARY**

#### # Wires

 Low
 7

 High
 0

 Coax
 0

 Triax
 0

 Quad
 0

 Fiber
 0

 Fluidic
 0

Series 0B

**Termination type** Female solder

IP rating 50

Cable Ø 5.30 - 5.60 mm

Matching parts FGG.0B.307.CLAD56

Status active

Alternative part



Image is for illustrative purpose only

## **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model PH\*: Free receptacle, cable collet

Keying 1 key (alpha=0, plug: male contacts, receptacle: female contacts)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

**Cable Fixing** D56: 5.3 - 5.6 mm

Variant

#### **Performance**

**Configuration** 0B.307 : 7 Low Voltage

Insulator L: PEEK (UL 94 / V-0/3.2, depends on material thickness)

Rated Current 2.5 Amps

#### **Specifications**

Contact Type: Solder Max. Matings: 5000

Contact Dia.: 0.5 mm (0.02in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 0.45 mm (0.018in)

Max. Solid Conductor: 0.09 mm<sup>2</sup> (AWG 28) Max. Stranded Conductor: 0.09 mm<sup>2</sup> (AWG 28)

R (max): 8.7 mOhm

Vtest (contact-shell): #700 V (AC), 990 V (DC) Vtest (contact-contact): 800 V (AC), 1130 V (DC)

#### **Others**

Endurance (Shell): 5000

Temp (min / max): -55°C / +250°C


Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [ 6 ms] Salt Spray Corrosion: >1000 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz)

IP Rating: 50

### **DRAWINGS**

#### **Draws**







#### **Dimensions**

	А	L	S1	S2
mm.	9.5	35.5	8	7
in.	0,37	1,40	0,31	0,28

## **RECOMMENDED BY LEMO**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

#### **Tools**

Spanner wrench: DCD.0B.005.PA070

#### **Cables**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.