

# LINEAR ACTUATOR TECHNICAL SPECIFICATION

Product Specification: MMACA24

| ITEM                                    | SPECIFICATION                       | NOTE                    |
|---|-------------------------------------|-------------------------|
| Power source rated voltage/Frequency    | 110-240V                            |                         |
| Switching power supply specified output | 29V/2A                              |                         |
| Electrical machinery rated voltage      | 29VDC                               |                         |
| Electrical machinery rated current      | 2ADC                                |                         |
| Electrical machinery rated power        | 58W                                 |                         |
| Idling current(Rise)                    | ≤0.7A                               |                         |
| Idling current(drop)                    | ≤1.5A                               |                         |
| Liad form                               | Push/Pull                           |                         |
| maximum thrust force                    | 6000N                               |                         |
| maximum pilling force                   | 4000N                               |                         |
| Protection rank                         | IP44                                |                         |
| Fixed working system                    | S2/18 2min ON 18min off             |                         |
| Installment dimension of high position  | 867±2mm                             |                         |
| Installment dimension of low position   | 1467±2mm                            |                         |
| Stroke                                  | 600±2mm                             |                         |
| Ldling traveling speed                  | 6.5±10%mm/s                         |                         |
| Vibration                               | Feel vibrated not obviously         |                         |
| Noise                                   | ≤55dB(A)                            | Test distance:<br>300mm |
| Contour and installation size           | Please see the outing drawing       |                         |
| Appearance                              | Nobroken,contanina tion or corroiss |                         |
|   | that would adversely effece either  |                         |
|   | the funtiong or the.unit            |                         |
| Life span                               | >10000times                         | Duty cycle:10%          |

Date/Draft:

Date/Check:

Date/Approve: