

## **Accessories Slim Interface Relay SNR**

- Module width 6.2 mm
- Reduced system width for increased packing density on the DIN rail
- **■** DC and AC version
- Electrical indicator as standard (LED)
- Protection circuit
- Screw- or cage clamp terminals
- Jumper bars
- RoHS compliant (Directive 2002/95/EC)




F0260


## **Approvals**

REG.-Nr. 6666, c Sus E224918

Technical data	ST3F/ST4F
Rated voltage / max. switching voltage AC	240 / 400 VAC
Rated current	6 A
Dielectric strength coil-contact circuit	4000 V <sub>rms</sub>
Clearance / creepage coil-contact circuit	≥ 6/8 mm
Material group of insulation parts	Illa
Insulation to IEC 60664-1	
Type of insulation coil-contact circuit	reinforced
open contact circuit	functional
Rated insulation voltage	250 V
Pollution degree	2
Rated voltage system	230 / 400 V
Overvoltage category	III
RoHS - Directive 2002/95/EC	compliant
Ambient temperature range	-20+55 °C
Terminals	screw / cage clamp
Terminal screw torque acc. IEC 61984	0.5 Nm
max.	0.6 Nm
Wire cross section	
single wire	0.142.5 mm <sup>2</sup>
fine wire	0.142.5 mm <sup>2</sup>
with bootlace crimp (DIN 46228/1)	0.142.5 mm <sup>2</sup>
Insertion cycles	A (10)
Max. Insertion Force total	100 N
Mounting distance	≥ 0 mm, dense packing
Weight	26 g
Packaging unit	10 pcs

Sockets					
Product code		Part Number			
ST 3F LC4	Din-rail socket 24VDC, for relays 12/24/48 VDC,	2-1416100-0			
	with LED, protection and polarity diode, screw terminals				
ST 3F SM5	Din-rail socket 115 VAC / VDC with LED and	2-1416100-1			
	protection circuit, screw terminals				
ST 3F TP0	Din-rail socket 230 VAC / VDC with LED and	2-1416100-2			
	protection circuit, screw terminals				
ST 4F LC4	Din-rail socket 24VDC, for relays 12/24/48 VDC,	2-1416100-3			
	with LED, protection and polarity diode,				
	cage clamp terminals				
ST 4F SM5	Din-rail socket 115 VAC / VDC with LED and	2-1416100-4			
	protection circuit, cage clamp terminals				
ST 4F TP0	Din-rail socket 230 VAC / VDC with LED and	2-1416100-5			
	protection circuit, cage clamp terminals				





Version with screw terminals

Version with cage clamp terminals





## Accessories Slim Interface Relay SNR (Continued)

Accessories		
Product code		Part Number
ST 36 040	Separation element	2-1416100-6
ST 37 001	Jumper bar, red, 500 mm	2-1416100-7
ST 37 002	Jumper bar, blue, 500 mm	2-1416100-8
ST 37 003	Jumper bar, grey, 500 mm	2-1416100-9
ST 37 040	Marking plate, consisting of 100 marking tabs	4-1416100-0

Rel	lav	<b>Packages</b>	

Complete packages consisting of a relay mounted on a socket: see Relay Package SNR