


# SLK-4A-S25



Item number 66.2017-\*

Highly flexible, with stackable Ø 4 mm MULTILAM plugs with rigid insulating sleeve on both ends.

Technical data	
Diameter of plug system	4 mm
Rated Values	1000 V, CAT II, 32 A / 600 V, CAT III, 32 A
Surface treatment electrical contact	Au
Base material electrical contact	CuZn
Standard color(s) *	<span style="background-color: #ffff00; padding: 2px;">20</span> <span style="background-color: #ff0000; padding: 2px;">21</span> <span style="background-color: #ff00ff; padding: 2px;">22</span> <span style="background-color: #0000ff; padding: 2px;">23</span> <span style="background-color: #00ff00; padding: 2px;">24</span> <span style="background-color: #00ff00; padding: 2px;">25</span> <span style="background-color: #ff00ff; padding: 2px;">26</span> <span style="background-color: #ff00ff; padding: 2px;">27</span> <span style="background-color: #ff00ff; padding: 2px;">28</span> <span style="background-color: #ff00ff; padding: 2px;">29</span> <span style="background-color: #ff00ff; padding: 2px;">30</span>
Lead lengths <input type="text"/>	025; 050; 075; 100; 150; 200 cm
Lead insulation	SIL
Lead cross section	2,5 mm <sup>2</sup>
Test accessory acc. to	IEC EN 61010-031
Approvals	UL, CE