

Mounted power supply
R Series

25W Single output
Approvals: CE,UL
Size(L×W×H):79mm×51mm×28mm

产品特性: <ul style="list-style-type: none"> ● 全范围AC输入 ● 通电指示灯 ● 过载/过压/短路保护 ● 小体积,高效率,高可靠性 ● 100%满载老化测试 ● 1`3年质保 		Product features: <ul style="list-style-type: none"> ● Universal AC input/ full range ● Power on indication ● Protections: Overload /Over voltage /Short circuit ● Compact, high reliability, high efficiency ● 100% full load burn-in test ● 1`3 years warranty 	
技术特性:		Specifications:	
输入电压 88~264VAC 常规100-240VAC	输入频率 47~63Hz	input voltage 88~264VAC Nominal 100-240VAC	Input frequency 47~63Hz
冲击电流 30A@230VAC, 全载冷态	维持时间 20ms@230 VAC 全载	Inrush current 30A @230VAC, full load cold start	Hold up time 20ms@230 VAC full load
过载保护 110%- 180%	过压保护 110%-140%	Overload protection 110%- 180%	Over voltage protection 110%-140%
运行温度 -20 ~70℃, 实据降额曲线	安全标准 UL60950-1	Operating temperature -20 ~ 70℃ refer to output derating curve	Safety standard UL60950-1
EMC标准 EN55022 class B	MTBF 20 ⁵ Hrs at 25℃	EMC standard EN55022 class B	MTBF 20 ⁵ Hrs at 25℃
绝缘标准 I/P-O/P: 3KV I/P-FG:1.5KV O/P-FG:0.5KV ,1min	重量 0.2Kg/pcs	Withstand voltage I/P-O/P: 3KV I/P-FG:1.5KV O/P-FG:0.5KV ,1min	Weight 0.2Kg/pcs

P/N	Output	Tol.	R&N	Effi.	Load Regulation	DC adjustment range
EPR-25-3.3	3.3V,6A	±4%	80mV	72%	±3%	3~3.6V
EPR-25-5	5V,5A	±3%	80mV	76%	±2%	4.75~5.25V
EPR-25-12	12V,2.1A	±3%	120mV	79%	±2%	10.8~13.2V
EPR-25-24	24V,1.1A	±3%	120mV	81%	±2%	21.6 V~26.4V
EPR-25-48	48V,0.57A	±3%	200mV	83%	±2%	43.2~52.8V