

**Mounted power supply
R Series**

150W Single output
Approvals: CE,UL
Size(L×W×H):199mm×98mm×38mm

产品特性: <ul style="list-style-type: none"> ● 全范围电压输入 ● 通电指示灯 ● 过载/过压/短路保护 ● 小体积,高效率,高可靠性 ● 100%满载老化测试 ● 1~3年质保 		Product features: <ul style="list-style-type: none"> ● Universal AC input/ full range ● Power on indication ● Protections: Overload /Over voltage /Short circuit ● Compact, high reliability, high efficiency ● 100% full load burn-in test ● 1~3 years warranty 	
技术参数:		Specifications:	
输入电压 输入频率 冲击电流 维持时间 过载保护 过压保护 运行温度 安全标准 EMC标准 MTBF 绝缘标准 重量	88~132VAC/176~264 VAC 拨动开关选择输入 47~63Hz 35A@230VAC, 全载冷态 20ms@230 VAC 全载 110%- 150% 110%-145% -20~ 70℃,实据降额曲线 UL60950-1 EN55022 class B 20 ⁵ Hrs at 25℃ I/P-O/P:3KV I/P-FG: 1.5KV,1min O/P-FG:0.5KV ,1min 0.7Kg/pcs	AC input voltage Input frequency Inrush current Hold up time Overload protection Over voltage protection Operating temperature Safety standard EMC standard MTBF Withstand voltage Weight	88-132VAC/176-264 VAC selected by switch 47~63Hz 35A @230VAC, full load cold start 20ms@230 VAC full load 110%- 150% 110%-145% -20 ~ 70℃ refer to output derating curve UL60950-1 EN55022 class B 20 ⁵ Hrs at 25℃ I/P-O/P:3KV,1min I/P-FG:1.5KV,1min O/P-FG:0.5KV ,1min 0.7Kg/pcs

P/N	Output	Tol.	R&N	Effi.	Load Regulation	DC adjustment range
EPR-150-3.3	3.3V,30A	±4%	80mV	74%	±3%	3~3.6V
EPR-150-5	5V,26A	±3%	80mV	77%	±2%	4.75~5.25V
EPR-150-12	12V,12.5A	±3%	120mV	83%	±2%	10.8~13.2V
EPR-150-24	24V,6.5A	±3%	120mV	86%	±2%	21.6 V~26.4V
EPR-150-48	48V,3.3A	±3%	200mV	87%	±2%	43.2~52.8V