

UPS SERIES | LINE INTERACTIVE



The Line Interactive UPS 1-3kVA is specially designed for personal computers and comes with multiple functions. Its lightweight and compact design make it a perfect fit for limited workspace environments.



LCD Color Display

Features

- ❖ Line Interactive UPS with simulated sinewave output
- ❖ Excellent microprocessor control guarantees high reliability (Internal self-diagnostic technology)
- ❖ Boost and buck AVR for voltage stabilization (One boost and one buck control)
- ❖ Auto restart while AC is recovering
- ❖ Cold start function
- ❖ Off-mode charging
- ❖ Fast intelligent battery recharge function
- ❖ Offering LED and LCD panels for selections Optional Generator compatible
- ❖ Optional USB/RS232 communication port and RJ45 protection



Socket



Rear Panel

- ① AC Input;
- ② Output Schuko
- ③ USB Communication
- ④ USB & RS232
- ⑤ RJ45

Technical Specifications

MODEL	KUTIN 800	KUTIN 1200	KUTIN 1500	KUTIN 2000	KUTIN 3000
Capacity (VA/W)	800/480	1200/720	1500/900	2000/1200	3000/1800
INPUT					
Nominal Voltage (Vac)		110/120 or 220/230/240			220/230/240
Operating Voltage Range (Vac)		81~145/162~290			162~290
OUTPUT					
AC Voltage Regulation (Batt. Mode)		±10%			
Frequency Range (Batt. Mode) (Hz)		60/50 ±1			
Transfer Time (ms)		Typical 2-6, 10 Max.			
Waveform (Batt. Mode)		Simulated Sinewave			
Number of Schuko	2	4	4	4	4
BATTERY					
Battery Voltage (Vdc)	12		24		48
Battery Capacity (Ah) & Nº (pcs)	9x1	7x2		9x2	9x4
Typical Recharge Time (hours)	4~6 recover to 90% capacity		6~8 recover to 90% capacity		
Typical backup times at 50 and 70% load*	3min	8min	6min	5min	10min
MANAGEMENT					
LED Display		AC Mode, Battery Mode, Overload, Fault			
LCD Display		AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault, and Battery Low			
Alarm		Battery mode, Battery low, overload, Battery replacement, Fault			
Communication Port		USB or RS232 (Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC)			
ENVIRONMENTAL					
Humidity		0~90%RH @ 0~40°C (Non condensing)			
Noise Level (dB)	<45		<55		
PHYSICAL					
Dimension WxDxH (mm)	298×101×142	353×149×162	380×158×198		436×145×212
Weight (kg)	4.9	8.4	10.1	10.5	23.0
STANDARDS					
Safety		IEC/EN 62040-1, IEC/EN 60950-1			
EMC		IEC/EN62040-2, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-8			

* Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

1. Specifications are subject to change without prior notice
2. Data above are typical values for reference only, not as a basis for engineering design

